

# Milano

## Specification / Imaging Guide

### 10 MIL Light Blocker | Thermal Backer

#### Specifications

**4 mil Polyester Primer**  
**1 mil White Extrusion**  
**1 mil Foil Primer**  
**4 mil White Co-extrusion**

#### Performance Characteristics

- For use as a backing film for high quality wide format graphics.
- End uses include posters, trade show graphics, and POP displays where high opacity and rigidity are required.
- 100% opacity.
- Increased bond strengths.
- Useable temperature range of 170°F to 245°F.

#### Technical Specifications

Typical Properties	Test Method	Units	Typical Value
<b>Gauge</b>	ASTM D645	Mils	9.5
<b>Yield</b>	Typical	In <sup>2</sup> / lb.	2,360
<b>Opacity</b>	ASTM 1003	% Transmission	0
<b>PET Side Coefficient of Friction</b>	ASTM D 1894	Kinetic	0.40
<b>Heat Seal Initiation Temperature</b>	@ 40psi, 0.5 sec. dwell	°F	170

[www.milanoinc.com](http://www.milanoinc.com)

For more information, please call 800-237-7347 Denver • Los Angeles • Chicago

Products and sizes subject to change. Suggestions made concerning uses, applications and compatibility are only the opinion of Milano. They are provided as a guide only and shall in no event constitute a warranty of any kind. The user assumes all risk from the use of these products and must confirm suitability thereof by his/her own tests. Our liability will in no event exceed the dollar value of the material sold. If at any time Milano-branded media fails to meet our specifications please return printed and unused portion for a full credit or exchange.

© 2007 MC Max Inc.