

Milano

Specification / Imaging Guide

10 MIL White Backer | Thermal Backer

Specifications

7 mil White Polyester Primer
3 mil White Co-extrusion

Performance Characteristics

- High performance thermal laminating film designed for use as a backing film for wide format graphics.
- End uses include posters, trade show graphics, and POP displays where high opacity and rigidity are required. Can be used for back-lit applications.
- Good opacity.
- Increased bond strengths.
- Useable temperature range of 170°F to 245°F.

Technical Specifications

Typical Properties	Test Method	Units	Typical Value
Gauge	ASTM D645	Mils	10
Yield	Typical	In ² / lb.	2,240
Opacity	ASTM 1003	% Transmission	19
PET Side Coefficient of Friction	ASTM D 1894	Kinetic	0.40
Heat Seal Initiation Temperature	@ 40psi, 0.5 sec. dwell	°F	170

www.milanoinc.com

For more information, please call 800-237-7347 Denver • Los Angeles • Chicago

Products and sizes subject to change. Suggestions made concerning uses, applications and compatibility are only the opinion of Milano. They are provided as a guide only and shall in no event constitute a warranty of any kind. The user assumes all risk from the use of these products and must confirm suitability thereof by his/her own tests. Our liability will in no event exceed the dollar value of the material sold. If at any time Milano-branded media fails to meet our specifications please return printed and unused portion for a full credit or exchange.

© 2007 MC Max Inc.