

# Milano

## Specification / Imaging Guide

### 1 Mil Tedlar® | Tedlar® Coated Film Overlamine

A 1.0 mil transparent Tedlar® film coated with 204-4100 permanent acrylic pressure sensitive adhesive on a 53# overlay liner. Recommended for use in overlay applications requiring extended resistance to UV exposure, color stability, abrasion resistance, chemical and graffiti resistance.

#### Specifications

<b>Thickness:</b>	Film	1.0 mil
	Liner	4.0 mil
	Adhesive	.8 to 1.0 mil
<b>Temperature Ranges:</b>	Minimum application temperature	+50° F
	Service temperature range	-40° F to +225° F
<b>Adhesion:</b>	48 oz/in	

#### Application Suggestions

Designed to extend the exterior exposure resistance of decals and nameplates. This overlay will protect inks and graphics from fading caused by exposure to UV radiation. Specifically designed for areas where graffiti and chemical resistance is required.

#### Storage Stability

Two years when stored at 70° F and 50% relative humidity.

[www.milanoinc.com](http://www.milanoinc.com)

For more information, please call 800-237-7347 Denver • Los Angeles • Chicago

Products and sizes subject to change. Suggestions made concerning uses, applications and compatibility are only the opinion of Milano. They are provided as a guide only and shall in no event constitute a warranty of any kind. The user assumes all risk from the use of these products and must confirm suitability thereof by his/her own tests. Our liability will in no event exceed the dollar value of the material sold. If at any time Milano-branded media fails to meet our specifications please return printed and unused portion for a full credit or exchange.

© 2007 MC Max Inc.