



Clear Gloss Tac | 3.5 mil Adhesive Vinyl Film

A 3.4-mil premium clear gloss calendered PVC film coated with removable acrylic pressure sensitive adhesive laminated to a 90# layflat liner.

Specifications

| | |
|------------------|----------|
| Film: | 3.4 mils |
| Adhesive: | 1 mil |
| Liner: | 6.7 mils |

Ink Compatibility

Designed to accept a variety of solvent-based inkjet and UV curable inks.

Applications

Designed for temporary interior or exterior signage, decals, nameplates, die-cut letters and point-of-purchase displays.

Typical Performance Values

| | |
|---|---|
| Minimum Application Temperature: | +40° F (minimum for substrate) |
| Service Temperature Range: | -40° F to +180° F |
| Adhesion: | 3 to 10 oz/in – to glass |
| Durability: | Clear vinyl film can yellow with exposure to UV radiation. Must be tested for specific usage. Removable up to 1 year under normal conditions. |
| Shelf life: | 6 month shelf life when stored at 70° F and 50% relative humidity |

Recommendations

Completely evaporate inkjet solvents before application. Failure to do so may facilitate solvent penetration resulting in vinyl degradation.

www.milanoinc.com

For more information, please call 800-237-7347 Denver • Los Angeles • Chicago

Products and sizes subject to change. Suggestions made concerning uses, applications and compatibility are only the opinion of Milano. They are provided as a guide only and shall in no event constitute a warranty of any kind. The user assumes all risk from the use of these products and must confirm suitability thereof by his/her own tests. Our liability will in no event exceed the dollar value of the material sold. If at any time Milano-branded media fails to meet our specifications please return printed and unused portion for a full credit or exchange.

© 2007 MC Max Inc.