



## PS10 UV PolyCarb | Pressure Sensitive Lamination Film

PS10 UV PolyCarb has a durable, embossed finish with UV enhanced, permanent, polyacrylic adhesive. Backed with a polyester release liner, it is good for either indoor or outdoor applications.

### Specifications

<b>Thickness:</b>	Film	10 mil Polycarbonate
	Liner	1.5 mil Polyester
	Adhesive	Clear Permanent Acrylic
<b>Temperature Ranges:</b>	Minimum application temperature	+50° F
	Service temperature range	-40° F to +176° F
<b>Adhesion:</b>	44 oz/in	

### Application Suggestions

Non-glare, very high clarity film. High UV/Fade resistance. High scuff and abrasion resistance. Velvet surface hides scratches and fingerprints.

Outstanding laminate for displays and point of purchase graphics.

### Storage Stability

1 year from ship date when stored in proper conditions.

[www.milanoinc.com](http://www.milanoinc.com)

For more information, please call 800-237-7347 Denver • Los Angeles • Chicago

Products and sizes subject to change. Suggestions made concerning uses, applications and compatibility are only the opinion of Milano. They are provided as a guide only and shall in no event constitute a warranty of any kind. The user assumes all risk from the use of these products and must confirm suitability thereof by his/her own tests. Our liability will in no event exceed the dollar value of the material sold. If at any time Milano-branded media fails to meet our specifications please return printed and unused portion for a full credit or exchange.

© 2007 MC Max Inc.