



PS15 UV PolyCarb | Pressure Sensitive Lamination Film

PS 15 UV PolyCarb is a pressure sensitive 15 mil velvet/very fine matte polycarbonate with the optically clear RD-60A permanent acrylic adhesive on a 3.0 mil polyester film liner. This polycarbonate film offers protection from abrasion, moisture and other environmental exposures. It is laminated by the cold laminating process without the addition of heat.

Specifications

Thickness:	Film	15 mil Polycarbonate
	Liner	3 mil Polyester
	Adhesive	1.4 to 1.6 mil
Temperature Ranges:	Minimum application temperature	+40° F
	Service temperature range	-40° F to +200° F
Adhesion:	44 oz/in	

Application Suggestions

Textured overlaminating film is designed to protect digital image prints and screen printed images for exhibit and display graphics. Can be used in most instances where an overlay with non-glare properties is required. This film can be used to produce flat, curved or rolled display graphics.

Storage Stability

1 year shelf life when stored at 70° F and 50% relative humidity.

www.milanoinc.com

For more information, please call 800-237-7347 Denver • Los Angeles • Chicago

Products and sizes subject to change. Suggestions made concerning uses, applications and compatibility are only the opinion of Milano. They are provided as a guide only and shall in no event constitute a warranty of any kind. The user assumes all risk from the use of these products and must confirm suitability thereof by his/her own tests. Our liability will in no event exceed the dollar value of the material sold. If at any time Milano-branded media fails to meet our specifications please return printed and unused portion for a full credit or exchange.

© 2007 MC Max Inc.