

Milano

Specification / Imaging Guide

PS UV Lustre | Pressure Sensitive Lamination Film

PS UV Lustre has a lustre finish with UV enhanced, permanent, polyacrylic adhesive. Backed with a 58# Polywhite release liner, it is good for either indoor or outdoor applications. UV protection added to vinyl.

Specifications

Thickness:	Film 3.2 mil PVC Liner 80 lb paper Adhesive Clear Permanent Acrylic
Temperature Ranges:	Minimum application temperature +40° F Service temperature range -40° F to +180° F
Adhesion:	To stainless steel 3.6 lbs/in.
UV Blocking:	200 N/m – 360 N/m at 100% 360 N/m – 400 N/m at 56%
Gloss/ 60° Gardner:	45-55 (avg.)

Application Suggestions

High grade film for indoor and outdoor protection and enhancement of photographs, posters, drawings, signs and other printed matter. Designed to provide a strong bond and UV protection.

Storage Stability

1 year from ship date when stored in proper conditions.

www.milanoinc.com

For more information, please call 800-237-7347 Denver • Los Angeles • Chicago

Products and sizes subject to change. Suggestions made concerning uses, applications and compatibility are only the opinion of Milano. They are provided as a guide only and shall in no event constitute a warranty of any kind. The user assumes all risk from the use of these products and must confirm suitability thereof by his/her own tests. Our liability will in no event exceed the dollar value of the material sold. If at any time Milano-branded media fails to meet our specifications please return printed and unused portion for a full credit or exchange.

