



## Polystyrene Translucent | 15mil Polystyrene

Polystyrene Translucent is a great option for backlit signage. This product is specially treated with a UV coating for optimum printing results. Excellent product for backlit signage. Plasticiser free formula, makes this product more environmentally friendly.

### Specifications

<b>Thickness:</b>	15 mil
<b>Tensile Strength (machine direction):</b>	2700 PSI
<b>Tensile Strength (cross direction):</b>	3500 PSI
<b>Tear Resistance:</b>	MD .15/lbs TD .39/lbs (initiated) MD 2.3/lbs TD 3.1/lbs (uninitiated)
<b>Dimensional Stability:</b>	Good

### Typical Performance Values

<b>Minimum application temperature:</b>	+50°F
<b>Adhesion:</b>	15 minutes 85oz. 24 hours 120 oz. PSTC-I, 180° peel @12"/min, 73°F, on Stainless Steel
<b>Shelf Life:</b>	2 years when stored at 74°F and 50% relative humidity

### Ink Compatibility

UV Curable Inks

### Applications

Tradeshow Signage  
Point of Purchase Displays

### Characteristics

Superior ink receptivity.  
Can be guillotine cut, die cut and punched.  
Excellent dimensional stability.

[www.milanoinc.com](http://www.milanoinc.com)

For more information, please call 800-237-7347 Denver • Los Angeles • Chicago

Products and sizes subject to change. Suggestions made concerning uses, applications and compatibility are only the opinion of Milano. They are provided as a guide only and shall in no event constitute a warranty of any kind. The user assumes all risk from the use of these products and must confirm suitability thereof by his/her own tests. Our liability will in no event exceed the dollar value of the material sold. If at any time Milano-branded media fails to meet our specifications please return printed and unused portion for a full credit or exchange.

© 2017 MC Max Inc.