



Polystyrene Translucent | 15mil Polystyrene

Polystyrene Translucent is a great option for backlit signage. This product is specially treated with a UV coating for optimum printing results. Excellent product for backlit signage. Plasticiser free formulation makes this product more environmentally friendly.

Specifications

Thickness:	15 mil
Tensile Strength (machine direction):	2700 PSI
Tensile Strength (cross direction):	3500 PSI
Tear Resistance:	MD .15/lbs TD .39/lbs (initiated) MD 2.3/lbs TD 3.1/lbs (uninitiated)
Dimensional Stability:	Good

Typical Performance Values

Minimum application temperature:	+50°F
Adhesion:	15 minutes 85oz. 24 hours 120 oz. PSTC-I, 180° peel @12"/min, 73°F, on Stainless Steel
Shelf Life:	2 years when stored at 74°F and 50% relative humidity

Ink Compatibility

Most large format UV/Latex printers.

Applications

Tradeshow Signage
Point of Purchase Displays

Characteristics

Superior ink receptivity.
Can be guillotine cut, die cut and punched.
Excellent dimensional stability.

www.milanoinc.com

For more information, please call 800-237-7347 Denver • Los Angeles • Chicago

Products and sizes subject to change. Suggestions made concerning uses, applications and compatibility are only the opinion of Milano. They are provided as a guide only and shall in no event constitute a warranty of any kind. The user assumes all risk from the use of these products and must confirm suitability thereof by his/her own tests. Our liability will in no event exceed the dollar value of the material sold. If at any time Milano-branded media fails to meet our specifications please return printed and unused portion for a full credit or exchange.

© 2007 MC Max Inc.