

Milano

Specification / Imaging Guide

Premium 36 | 36 lb Coated Adhesive

One side heavy coated inkjet paper with a high white matte surface and a permanent self-adhesive reverse side.

Specifications

Basis Weight (Total)	140g/m ²	Brightness	104	Ink Compatibility
Caliper (Mils)	7.6			Dye based and pigmented inks

Application Suggestions

It prints brilliant colors with both piezo and thermal print heads using both dye and pigmented inks. It dries instantly; exhibits high water resistance, and laminates well with both thermal and pressure sensitive films. It is perfect for presentations, courtroom graphics, simple graphics and line or text work.

Imaging Guidelines

Printing: Premium 36 is compatible with most ink systems (wide and small formats). Instant dry. Excellent water resistance on print image.

Media Handling: Media should be allowed to acclimate for 48 hours in the printing environment before use. The use of cotton gloves when handling may prevent transfer of oil and dirt to the print surface, which could affect print quality.

Storage/Printing Environment: It is recommended to store and print on this media in a controlled environment at a temperature between 50 - 85° F and a relative humidity between 30 - 65 percent.

Finishing Recommendations

Lamination: This media is compatible with both thermal and pressure-sensitive lamination films. It has been tested with various types of lamination films and no incompatibilities were found.

Laminators: As a guideline, we recommend a "low-melt" film laminating at approximately 205° F with a speed of around 5 fpm. When laminating with PSA films, a heat-assist of approximately 120° F on the top roller at a speed of around 3 fpm is recommended. These specs can greatly vary from machine to machine and can also be affected by your environment.

Mounting: Mounting prints can be easily done with pressure-sensitive mounting materials or spray adhesives applied directly to the mounting substrate.

Handling: When laminating with a PSA laminate, a curing time of 24 hours is recommended in order to allow the adhesive to achieve optimum strength.

Shipping/Delivery: When preparing a piece to transport, roll the laminated image print-side out as **LOOSE** as possible; this will help avoid tunneling.

www.milanoinc.com

For more information, please call 800-237-7347 Denver • Los Angeles • Chicago

Products and sizes subject to change. Suggestions made concerning uses, applications and compatibility are only the opinion of Milano. They are provided as a guide only and shall in no event constitute a warranty of any kind. The user assumes all risk from the use of these products and must confirm suitability thereof by his/her own tests. Our liability will in no event exceed the dollar value of the material sold. If at any time Milano-branded media fails to meet our specifications please return printed and unused portion for a full credit or exchange.

© 2007 MC Max Inc.