



Crystal Clear Mount | Pressure Sensitive Mounting Film

A 1 mil optically clear polyester mounting adhesive coated on both sides with a 1 mil optically clear permanent acrylic adhesive with a 1.2 silicone coated polyester liner on top and bottom.

Specifications

Thickness:	Film	1 mil Optically Clear Polypropylene
	Liner	2 mil One-Sided Silicone-Coated Clear Film
	Adhesive	Optically Clear Permanent Acrylic
	Total	6 mil
Temperature Ranges:	Minimum application temperature	+40° F
	Service temperature range	0° F to +212° F
Adhesion:	12 +/- N/inch	

Application Suggestions

Window, glass doors or any transparent surface when see-through graphics are needed for promotional advertising and point of purchase in retailers; eye-catching exhibit booths at trade shows.

Storage Stability

1 year from ship date when stored in proper conditions.

www.milanoinc.com

For more information, please call 800-237-7347 Denver • Los Angeles • Chicago

Products and sizes subject to change. Suggestions made concerning uses, applications and compatibility are only the opinion of Milano. They are provided as a guide only and shall in no event constitute a warranty of any kind. The user assumes all risk from the use of these products and must confirm suitability thereof by his/her own tests. Our liability will in no event exceed the dollar value of the material sold. If at any time Milano-branded media fails to meet our specifications please return printed and unused portion for a full credit or exchange.

© 2007 MC Max Inc.